
















Signature Primes

				
Name	ARRI SIGNATURE PRIME 12/T1.8	ARRI SIGNATURE PRIME 15/T1.8	ARRI SIGNATURE PRIME 18/T1.8	ARRI SIGNATURE PRIME 21/T1.8
Lens mount	LPL	LPL	LPL	LPL
LDS	LDS-2 or Cooke/i	LDS-2 or Cooke/i	LDS-2 or Cooke/i	LDS-2 or Cooke/i
MOD from sensor plane (minimum marked distance)	0.35 m / 14"	0.35 m / 14"	0.35 m / 14"	0.35 m / 14"
MOD from lens front	0.07 m / 2.6"	0.1 m / 4.3"	0.13 m / 5.1"	0.13 m / 5"
Length from flange	239 mm / 9.41"	197 mm / 7.75"	178 mm / 7.01"	178 mm / 7.01"
Magnification ratio at MOD (paraxial)	1:7.0	1:10.3	1:9.2	1:8.2
Entrance pupil position (related to image plane, in direction to object)	262.5 mm / 10.34"	203.0 mm / 7.99"	189.5 mm / 7.46"	183.4 mm / 7.22"
Angle of view	114.2° / 94.0° / 124.0°	102.0° / 81.2° / 112.9°	91.4° / 71.0° / 102.6°	82.7° / 63.0° / 94.0°
H - V - D for LF Open Gate				
Front diameter	134 mm / 5.28"	156 mm / 6.14"	114 mm / 4.49"	114 mm / 4.49"
Maximum housing diameter	135 mm / 5.31"	157 mm / 6.18"	115 mm / 4.52"	115 mm / 4.52"
Weight (lens only)	2.8 kg / 6.2 lb	2.8 kg / 6.1 lb	2.0 kg / 4.4 lb	1.9 kg / 4.2 lb

				
Name	ARRI SIGNATURE PRIME 25/T1.8	ARRI SIGNATURE PRIME 29/T1.8	ARRI SIGNATURE PRIME 35/T1.8	ARRI SIGNATURE PRIME 40/T1.8
Lens mount	LPL	LPL	LPL	LPL
LDS	LDS-2 or Cooke/i	LDS-2 or Cooke/i	LDS-2 or Cooke/i	LDS-2 or Cooke/i
MOD from sensor plane (minimum marked distance)	0.35 m / 14"	0.35 m / 14"	0.35 m / 14"	0.35 m / 14"
MOD from lens front	0.13 m / 5.1"	0.13 m / 5"	0.13 m / 5"	0.13 m / 5"
Length from flange	178 mm / 7.01"	178 mm / 7.01"	178 mm / 7.01"	178 mm / 7.01"
Magnification ratio at MOD (paraxial)	1:7.1	1:6.4	1:5.4	1:4.8
Entrance pupil position (related to image plane, in direction to object)	177.6 mm / 7.00"	165.8 mm / 6.53"	162.1 mm / 6.38"	159.3 mm / 6.27"
Angle of view	73.0° / 54.4° / 84.0°	65.1° / 47.9° / 75.7°	55.5° / 40.2° / 65.3°	49.3° / 35.4° / 58.3°
H - V - D for LF Open Gate				
Front diameter	114 mm / 4.49"	114 mm / 4.49"	114 mm / 4.49"	114 mm / 4.49"
Maximum housing diameter	115 mm / 4.52"	115 mm / 4.52"	115 mm / 4.52"	115 mm / 4.52"
Weight (lens only)	1.9 kg / 4.2 lb	1.8 kg / 4.0 lb	1.7 kg / 3.7 lb	1.8 km / 4.0 lb

					
Name	ARRI SIGNATURE PRIME 47/T1.8	ARRI SIGNATURE PRIME 58/T1.8	ARRI SIGNATURE PRIME 75/T1.8	ARRI SIGNATURE PRIME 95/T1.8	ARRI SIGNATURE PRIME 125/T1.8
Lens mount	LPL	LPL	LPL	LPL	LPL
LDS	LDS-2 or Cooke/i	LDS-2 or Cooke/i	LDS-2 or Cooke/i	LDS-2 or Cooke/i	LDS-2 or Cooke/i
MOD from sensor plane (minimum marked distance)	0.45 m / 18"	0.45 m / 18"	0.65 m / 26"	0.85 m / 2' 9"	1 m / 3' 4"
MOD from lens front	0.23 m / 9.0"	0.23 m / 9.0"	0.43 m / 17"	0.63 m / 2' 1"	0.78 m / 2' 7"
Length from flange	178 mm / 7.01"	178 mm / 7.01"	178 mm / 7.01"	178 mm / 7.01"	178 mm / 7.01"
Magnification ratio at MOD (paraxial)	1:6.3	1:5.4	1:7.2	1:7.9	1:7.0
Entrance pupil position (related to image plane, in direction to object)	155.8 mm / 6.13"	143.9 mm / 5.66"	115.5 mm / 4.55"	85.4 mm / 3.36"	52.6 mm / 2.07"
Angle of view	42.6° / 30.4° / 50.8°	34.9° / 24.8° / 41.8°	27.5° / 19.3° / 33.3°	21.6° / 15.3° / 26.5°	16.6° / 11.6° / 20.2°
H - V - D for LF Open Gate					
Front diameter	114 mm / 4.49"	114 mm / 4.49"	114 mm / 4.49"	114 mm / 4.49"	114 mm / 4.49"
Maximum housing diameter	115 mm / 4.52"	115 mm / 4.52"	115 mm / 4.52"	115 mm / 4.52"	115 mm / 4.52"
Weight (lens only)	1.8 kg / 4.0 lb	2.0 kg / 4.4 lb	1.9 kg / 4.2 lb	1.9 kg / 4.2 lb	2.3 kg / 5.1 lb

				
Name	ARRI SIGNATURE PRIME 150/T1.8	ARRI SIGNATURE PRIME 200/T2.5	ARRI SIGNATURE PRIME 280/T2.8	ARRI SIGNATURE PRIME 280/T2.8 + 1.7x EXTENDER
Lens mount	LPL	LPL	LPL	LPL
LDS	LDS-2 or Cooke/i	LDS-2 or Cooke/i	LDS-2 or Cooke/i	-
MOD from sensor plane (minimum marked distance)	1.5 m / 5'	1.8 m / 6'	2.5 m / 8' 3"	2.54 m / 8.38' (2.5 m / 8' 3")
MOD from lens front	1.25 m / 4' 2"	1.54 m / 5' 1"	2.18 m / 7' 2"	2.18 m / 7' 2"
Length from flange	208 mm / 8.19"	218 mm / 8.58"	278 mm / 10.93"	Extender: 53.78 mm / 2.1" Extension by Extender: 36.8 mm / 1.4" Lens + Extender: 314.8 mm / 12"
Magnification ratio at MOD (paraxial)	1:9.0	1:8.3	1:8.3	1:4.7
Entrance pupil position (related to image plane, in direction to object)	54.5 mm / 2.15"	34.9 mm / 1.37"	36.9 mm / 1.45"	73.73 mm
Angle of view	13.9° / 9.7° / 16.9°	10.4° / 7.3° / 12.6°	7.4° / 5.2° / 9.0°	4.7° / 3.1° / 5.5°
H - V - D for LF Open Gate				
Front diameter	114 mm / 4.49"	114 mm / 4.49"	134 mm / 5.28"	134 mm / 5.28"
Maximum housing diameter	135 mm / 5.31"	135 mm / 5.31"	135 mm / 5.31"	Extender only: 114 mm / 4.5" including handles - 135 mm / 5.31" with lens
Weight (lens only)	3.25 kg / 7.3 lb	3.1 kg / 6.13 lb	4.3 kg / 9.48 lb	Extender : 0.58 kg / 1 lb 4 oz - Lens + Extender: 4.9kg / 10 lb 13 oz